

SID

Factory: Rot am See

Article:

662

ML6

Provided:

Stockburger, Olesja

Customer:

Date:

21.01.2016



Processtechnology: B: undefiniert

Material Text	Mat. Nr.	µm	Stackup	Process overview
A-RS Kupferfolie-035my 330x490mm	50200242	35	VS	1
A-RS-FR4-Prepreg-2116-TG150-HF	50200642	200		2
A-RS-FR4-Prepreg-2116-TG150-HF	50200642	0		3
A-RS-FR4-Prepreg-1080-TG150-HF	50200641	50		4
C-RS-FR4-ML-0.51mm-105+105-TG150-HF	50200884	105	L2	5
		510		
		105	L3	
A-RS-FR4-Prepreg-1080-TG150-HF	50200641	45		6
A-RS-FR4-Prepreg-2116-TG150-HF	50200642	180		7
A-RS-FR4-Prepreg-2116-TG150-HF	50200642	0		8
A-RS-FR4-Prepreg-1080-TG150-HF	50200641	45		9
C-RS-FR4-ML-0.51mm-105+105-TG150-HF	50200884	105	L4	10
		510		
		105	L5	
A-RS-FR4-Prepreg-1080-TG150-HF	50200641	50		11
A-RS-FR4-Prepreg-2116-TG150-HF	50200642	200		12
A-RS-FR4-Prepreg-2116-TG150-HF	50200642	0		13
A-RS Kupferfolie-035my 330x490mm	50200242	35	RS	14

Thickness after Pressing

B00:

2290 µm

Tol+:

240 µm

Tol-:

240 µm

Dmax:

2530 µm

Dmin:

2050 µm

Thickness over all

0 µm

Tol+:

0 µm

Tol-:

0 µm

Dmax:

0 µm

Dmin:

0 µm

Demand for customer

Thickness (D):

2400 µm

Tol+:

240 µm

Tol-:

240 µm

Dmax:

2640 µm

Dmin:

2160 µm

Measuring point: (05) über LM und galv.Cu; beidseitig

nominal:

2280 µm

Version 1.2.14.15

© Würth Elektronik